




PRODUCTS YOU PROFIT FROM

# LT56-2

## Rugged Universal Laser Layout Tool



### Key Features and Benefits

- Bright crisp laser lines - extends the working range and are easy to see
- Lithium-Ion batteries provide 25 hour operating time - huge savings on battery cost compared to alkaline models and are ecological friendly
- Rugged and durable - 3 foot (1m) drop specification means the LT56-2 can keep working even after minor accidents
- Versatile mounting accessory - includes ceiling track, magnetic and tripod mounts with rotation and fine vertical adjustment
- The HR1220 detector is added for exterior short range applications
- 3-year instant exchange warranty

### Applications

- Wall layout
- Framing alignment
- Point transfer
- Acoustical ceiling installation
- Cabinet and trim installation
- Tile layout and installation
- Short range exterior leveling

Part No.	Points	Bracket	Target	Case	Batteries
LT56-2 (524022)	3 beams	Included	HR 1220 detector included	Hard case included	Included





PRODUCTS YOU PROFIT FROM

## One Tool Does It All

### LT56-2 (524022) Laser Specifications

- Laser Power: Less than 1mw
- Class/Wavelength: Class 2 / 635nm
- Batteries: Lithium-ion, 7200 mAh, 3.7 V
- Battery Life: 1 beam - 45 hours  
2 beam - 35 hours  
3 beam - 25 hours
- Charge Time: 12 hours (30 minute quick charge will provide 2 hours operation with 2 beams)
- Battery Warranty: 2 years
- Charger: Input: 100-240V AC 190 mA  
Output: 5V DC 800mA
- Out of Level Indication: Flashing beam - triple flash every 10 seconds
- Self Leveling Range: 4° ±1° all direction
- Dust and Water Resistance: IP54
- Operating Temperature: -10° to 45° (14 °F to 113 °F)
- Storage Temperature: -20° to 60° (-4 °F to 140 °F)
- Size: (L x W x H) 152 x 116 x 84 mm (4.6 x 6.0 x 3.3 in)
- Weight: 0.67 kg (1.48 lb)



LT56-2 features a strong metal sunshade

### HR1220 Receiver Specifications

- Digital Readout Units: mm, ft, in, fraction
- Reception Height: 4 in (102 mm)
- Three On-grade Sensitivities:  
Fine: 1/16 in (1 mm)  
Medium: 1/4 in (5 mm)  
Calibration Mode: 1/64 in (0.1 mm)
- Battery Life (2 x AA): 70+ hrs
- Automatic Shut-off: 30 minutes
- Operating Temp.: -4°F to 122°F (-20°C to 50°C)
- Dust & Waterproof: Yes IP67
- Weight without Clamp: 13.1 oz (0.371 kg)
- Warranty: 3 Years, 2 Years "No Excuses"



HR1220 receiver and C45 rod clamp optional



LT56-2 package with HR1220 receiver